

PRODUCT-DETAILS



Front



General Information		
Global Commercial Alias	AF82FPNM	
Extended Product Type	AF82FPNM	
Product ID	1TQR382200D1300	
EAN	not available	
Catalog Description	Front	
Long Description	ReliaGear lighting panelboards are factory assembled on rigid steel frames and equipped with circuit breakers from 15 A to 800 A. The maximum fully-rated short circuit rating is equal to 65 kAIC to 240 V AC and 480/277 V AC.	

ABB EcoSolutions	
ABB EcoSolutions	Yes
Circular Design Principles Recyclability Rate	92.6 %
Offered with Extended Lifetime	Product Modularity
End of Life Instructions	1SQC173021M0202
Environmental Product	1SQC173004D0201

© 2024 ABB. All rights reserved.

2024/10/15

Subject to change without notice

Dimensions	
Product Net Width	21.250 ir
Product Net Height	82.500 ir
Product Net Depth / Length	0.100 ir
Product Net Weight	52.000 lk
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	67.790 lk
Certificates and Declarations	
Declaration of Conformity - CE	No declaration needed
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical Information	9AKK107680A9334
Classifications	
WEEE Category	Product Not in WEEE Scope
UNSPSC	39121321
IDEA Granular Category Code (IGCC)	4465 >> Enclosure General Accessories

## Categories

© 2024 ABB. All rights reserved.

Subject to change without notice

Low Voltage Products and Systems  $\rightarrow$  NEMA Residential and Commercial Portfolio  $\rightarrow$  Lighting Panels & Breakers  $\rightarrow$  ReliaGear Lighting Panels

